

SAGEM HILO

GPRS M2M modules

*The smallest concentrate of
technology in the world*



**FREEDOM OF SPEECH
FOR SMART MACHINES**

SAGEM HILO

GPRS M2M modules

GSM, GPRS Class 10

Full Quad band Support: 850/900/1800/1900 MHz

Extremely small Form Factor (27mm X 27 mm X 3.6 mm)

Extremely light weight (< 4 g.)

Extended operational temperature range (from -40°C up to +85°C)

Very low power consumption (< 1,5 mA in Idle mode)

Complete embedded Internet connectivity

Ruggedized design for automotive & industrial applications



SAGEM introduces its new GPRS solution for all your M2M applications:

- Smallest GPRS module available on the market, SAGEM HiLo perfectly suits all your applications for which size matters! (Track&trace, POS, security...)
- Thanks to its extremely low power consumption, SAGEM HiLo increases the autonomy of your battery-powered applications (POS, Track&trace, security phones...)
- With its extended t° range, SAGEM HiLo understands your specific automotive requirements.
- Last but not least, thanks to its very competitive positioning, SAGEM HiLo creates new possibilities for all your cost-driven applications (Metering...)

Moreover, by choosing SAGEM, you decide to choose:

- A world class manufacturer who controls its own production capacity
- A technology validated and approved worldwide
- A top of the range technical support
- The highest standards of quality

TECHNICAL FEATURES

ENVIRONMENT

- 40 Pins Industrial approved Connector
- Size (LxWxH,mm): 27 x 27 x 3.6 mm
- Weight: < 4 g.
- Operational Temperature range: -40°C / +85 °C
- Power supply DC voltage (min / max / nominal): 3.2 V / 4.5 V / 3.6 V
- Antenna Connection & Detection through 50 ohms RF connector or Antenna pad
- Full Type Approved: R&TTE, GCF, PTCRB, FCC, Rohs Compliancy
- Consumption in Standby mode (can receive a call): < 1.5 mA
- Consumption in off mode: < 50 uA
- Enhanced mechanical integration for ruggedised environment

RADIO LINK

- Full Quad Band: EGSM 850, 900, 1800, 1900
- Output Power: Class 4 (2W) for 850 / 900 Mhz ; Class 1 (1W) for 1800 / 1900 Mhz
- GPRS Multislot Class: class 10 (3+2 & 4+1)
- GPRS baudrates: DL up to 85,6 kbps, UL up to 42,8 kbps
- GPRS Coding Scheme: CS1 to CS 4
- Mobile Station Class B

DATA INTERFACES

- 2 serial Interfaces (incl. one for internal traces)
- Full Hardware and Software Flow Control
- AT commands set: GSM 07.05; 07.07; 07.10, Proprietary AT commands
- Multiplexing 07.10 serial interface
- Data over CSD 9,6 kbps, Fax
- Complete internet connectivity embedded: TCP, FTP, UDP, SMTP, POP3...
- 5 generals I/O & 1 ADC

AUDIO INTERFACE

- Voice codecs: HR, EFR, FR, AMR
- Analog audio interface
- Echo Cancellation & Noise reduction

GSM FEATURES

- Automatic hang up for Data call
- Internal Phonebook
- CLIP / CLIR / COLP / COLR
- Call wait / call hold, Conference call
- Call forwarding, Call Barring
- Supports of: FDN, USSD, Sim Toolkit, AoC
- PDU and Text mode SMS support
- MMS support (dedicated AT commands)
- Module reset/alarm based on RTC

LOCALIZATION

- SMS CB, Cell ID
- Network cells measurements

SECURITY

- Sim lock supported
- Device lock possibility
- Dedicated TAC for Customization purpose
- Sim 3V & 1.8 V supported

DEVELOPMENT AND SUPPORT TOOLS

- Extensive Documentations: HW Specs, Application Note, AT command list, pedagogical documentations
- Development board
- Evaluation software tools (TCP-IP, MMS, 07.10 protocol, ...)
- Audio settings tool
- Upgrade tools
- Design, Certification & production support

All rights reserved. The information and specifications included are subject to change without prior notice. Sagem Communications tries to ensure that all information in this document is correct, but does not accept liability for error or omission. Non contractual document. All trademarks are registered by their respective owners. Limited company - Capital 167.038.185 Euro - 440 294 510 RCS Paris - SAGEM is a registered brand from Safran Group. 05/2007

Sagem Communications
Systems & Partnerships Business Unit
Radio & Professional Terminal Department

Headquarters: Le Ponant de Paris
27, rue Leblanc - 75015 Paris - FRANCE
Tel: +33 1 53 23 18 16 - Fax: +33 1 58 12 42 95

www.sagem.com

